

STENHEIM

REFERENCE
STATEMENT



REFERENCE STATEMENT

STENHEIM will take the world of passionate audiophiles by storm, with its improved version of state-of-the art speaker.

This speaker system (4 towers) was created in pure and well-studied lines to create not only a superb look, but unparalleled sound rendition, based on the concept behind the already well-reputed REFERENCE. It will enthrall future owners with its exceptional dynamic and musicality, its three-dimensional space, and vibrantly alive, natural soundstage.

Then there's its flawless rendering of any genre of music, along with impressive sound levels from the deepest bass to the highest notes.

The REFERENCE STATEMENT is also distinct in its exceptional ease-of-use, thanks to remote operation of the MTM couple (Medium Tweeter Medium) diffusion angle. It also adapts to all amplification systems and rooms, thanks to a medium-bass-sub bass frequency crossover included in a separate housing unit that inserts between the pre-amp and the amps.

Forget technology, simply experience music.



- **REFERENCE speaker system:**
 - 2 Reference full range speakers with 2 x 9 transducers in full d'Appoliton configuration
 - 2 Reference sub towers with 2 x 6 transducers
- 12 x 13 inches high excursion woofers, 8 x 13 inches bass units (new), 4 x 6.5 inches neodymium medium drivers, 2 x neodymium tweeters and 4 x ribbon supertweeters
- 4 massive aluminum cabinets with 24 independent closed chambers
- Motorized angle deviation of the MTM section
- Passive-active 5 ways system, with 2 analogue active mono crossovers for bass and sub woofer section
- **Frequency response:** 10Hz to 100kHz
- **Power handling:**
 - Sub Tower: 3600W
 - Bass section: 1400 W
 - Medium-tweeter section : 300 W
- **Sensitivity:** 96 dB
- **Dim:** 4 x H1890mm x W370mm x D 560 mm
- **Weight:** 4 x 300 Kg (including Ultimate REFERENCE Stands)
- **Warranty:** 5 years